

AMENDMENTS TO THE CLAIMS

C1  
Claim 1. (original) A modular electrical component, comprising:  
a base unit having a plurality of first terminal members, and a plurality of second  
terminal members connectable to conductors in an electrical wiring system;  
5 a mounting strap secured to a rear cover of said base and capable of connecting  
said base to a junction box in the electrical wiring system; and  
a removable electrical device having a plurality of power contacts extending from  
a rear cover and capable of releasably connecting to said plurality of first terminal  
members, such that one of said plurality of contacts releasably connects to one of said  
10 plurality of said first terminal members.

Claim 2. (original) The modular electrical component according to claim 1,  
wherein said mounting strap has at least one ground terminal connection that extends into  
said base unit, and wherein said removable electrical device has at least one ground  
15 contact extending from said rear cover, said at least one ground contact is capable of  
being releasably connected to said at least one ground terminal connection.

Claim 3. (original) The modular electrical component according to claim 1,  
wherein said removable electrical device comprises a receptacle.  
20

Claim 4. (original) The modular electrical component according to claim 1,  
wherein said removable electrical device comprises a switch.

Claim 5. (original) The modular electrical component according to claim 1,  
25 wherein said removable electrical device comprises a circuit interrupting device.

----- Claim 6. (original) The modular electrical component according to claim 5; -----  
wherein said circuit interrupting device comprises:  
a housing;

a line side conductive path disposed at least partially within said housing and connected to at least one of said plurality of power contacts;

a load side conductive path disposed at least partially within said housing and connected to at least one of said plurality of power contacts;

5 a circuit interrupting portion disposed at least partially within said housing and configured to break the continuity between said line side and load side conductive paths upon the occurrence of a predetermined condition;

a reset portion disposed at least partially within said housing and configured to make electrical continuity between said line side and said load side conductive paths; and

10

Claim 7. (original) The modular electrical component according to claim 6 further comprising a reset lockout that prevents the making of electrical continuity between said line side and load side conductive paths if said circuit interrupting portion is non-operational.

15

Claim 8. (original) The modular electrical component according to claim 7 further comprising a trip portion disposed at least partially within said housing and configured to break the continuity between said line side and load side conductive paths independently of said circuit interrupting portion operation.

20

Claim 9. (original) The modular electrical component according to claim 7, wherein said circuit interrupting portion comprises sensing circuitry used to sense the occurrence of said predetermined condition, and wherein said reset portion comprises:

a reset button operatively coupled to said reset lockout; and

25

a reset contact electrically connected to said sensing circuitry, such that depression of said reset button causes one of said line side or load side conductive path to contact said reset contact and activate said circuit interrupting portion to break the continuity between said line side and load side conductive paths upon the occurrence of a predetermined condition.

30

Claim 10. (original) The modular electrical component according to claim 6, wherein said circuit interrupting device comprises a GFCI receptacle, and wherein said predefined condition comprises a ground fault.

5           Claim 11. (original) The modular electrical component according to claim 6, wherein said circuit interrupting portion includes a circuit interrupter used to facilitate making and breaking of electrical continuity between said line side and load side conductive paths, and sensing circuitry used to sense the occurrence of said predetermined condition.

10

C/           Claim 12. (original) The modular electrical component according to claim 1, wherein said base unit is configured to fit within a single gang junction box in the electrical wiring system.

15           Claim 13. (original) The modular electrical component according to claim 1, wherein said base unit is configured to fit within a multiple gang junction box in the electrical wiring system.

20           Claim 14. (original) A modular electrical component, comprising:  
a removable electrical device having a plurality of power contacts extending from a rear cover of said removable electrical device;  
a base unit configured to fit within a junction box of an electrical wiring system, said base unit having a plurality of terminal connections, wherein each terminal connection is connectable to at least one conductor in the electrical wiring system and to  
25 at least one of said power contacts; and  
a mounting strap secured to a rear cover of said base unit and capable of connecting said base unit to the junction box in the electrical wiring system.

30           Claim 15. (original) The modular electrical component according to claim 14, wherein said mounting strap has at least one ground terminal connection that extends into said base unit, and wherein said removable electrical device has at least one ground

contact extending from said rear cover, said at least one ground contact is capable of being releasably connected to said at least one ground terminal connection.

Claim 16. (original) The modular electrical component according to claim 14,  
5 wherein said removable electrical device comprises a receptacle.

Claim 17. (original) The modular electrical component according to claim 14,  
wherein said removable electrical device comprises a switch.

10 Claim 18. (original) The modular electrical component according to claim 14,  
wherein said removable electrical device comprises a circuit interrupting device.

Claim 19. (original) The modular electrical component according to claim 18,  
wherein said circuit interrupting device comprises:

- 15 a housing;  
a first electrical conductive path disposed at least partially within said housing and  
connected to at least one of said plurality of power contacts;  
a second electrical conductive path disposed at least partially within said housing  
and connected to at least one of said plurality of power contacts;  
20 a circuit interrupting portion disposed at least partially within said housing and  
configured to break the continuity between said first and second conductive paths upon  
the occurrence of a predetermined condition; and  
a reset portion disposed at least partially within said housing and configured to  
make electrical continuity between the first and second conductive paths.

25 Claim 20. (original) The modular electrical component according to claim 19  
further comprising a reset lockout portion that prevents the making of electrical  
continuity between said first and second conductive paths if said circuit interrupting  
portion is non-operational.

30

Claim 21. (original) The modular electrical component according to claim 20 further comprising a trip portion disposed at least partially within said housing and configured to break the continuity between said first and second conductive paths independently of said circuit interrupting portion operation.

5

Claim 22. (original) The modular electrical component according to claim 19, wherein said circuit interrupting portion includes a circuit interrupter used to facilitate making and breaking of electrical continuity between said first and second electrical conductive paths, and sensing circuitry used to sense the occurrence of said predetermined condition.

10

Claim 23. (original) The modular electrical component according to claim 14, wherein said circuit interrupting device comprises a GFCI receptacle and said predefined condition comprises a ground fault.

15

Claim 24. (original) The modular electrical component according to claim 14, wherein each of said terminal connections comprise:

a first terminal member connectable to one of said plurality of contacts extending from said rear of said removable electrical device; and

20 a second terminal member connectable to at least one conductor in the electrical wiring system.

Claim 25. (original) A modular electrical component, comprising:

25 a removable electrical device having a plurality of power contacts extending from a rear cover of said removable electrical device;

connecting means configured to fit within a junction box of an electrical wiring system for connecting said plurality of power contacts to at least one conductor in the electrical wiring system; and

30 mounting means associated with said connecting means for mounting said connecting means to the junction box in the electrical wiring system.

Claim 26. (original) The modular electrical component according to claim 25, wherein said removable electrical device has at least one ground contact extending from said rear cover, and wherein said mounting means includes means for connecting said at least one ground contact to a ground of said electrical wiring system.

5

Claim 27. (original) The modular electrical component according to claim 25, wherein said removable electrical device comprises a receptacle.

Claim 28. (original) The modular electrical component according to claim 25,  
10 wherein said removable electrical device comprises a switch.

Claim 29. (original) The modular electrical component according to claim 25,  
wherein said removable electrical device comprises a circuit interrupting device.

15 Claim 30. (original) The modular electrical component according to claim 29,  
wherein said circuit interrupting device comprises:

a housing;

means associated with said plurality of power contacts for conducting electricity  
between a line side and a load side of said circuit interrupting device;

20 circuit interrupting means for breaking continuity between said line side and said  
load side of said circuit interrupting device upon the occurrence of a predetermined  
condition; and

reset means for reestablishing electrical continuity between said line side and said  
load side of said circuit interrupting device.

25

Claim 31. (original) The modular electrical component according to claim 30  
further comprising reset lockout means for preventing said reset means from  
reestablishing electrical continuity between said line side and said load side of said circuit  
interrupting device when said circuit interrupting portion is non-operational.

30

Claim 32. (original) The modular electrical component according to claim 31 further comprising trip means for breaking continuity between said line side and said load side of said circuit interrupting device independently of the operation of said circuit interrupting means.

5

Claim 33. (original) The modular electrical component according to claim 30, wherein said circuit interrupting device comprises a GFCI receptacle and said predetermined condition comprises a ground fault.

10

Claim 34. (original) The modular electrical component according to claim 30, wherein said circuit interrupting means comprises a circuit interrupter used to facilitate making and breaking of electrical continuity between said line side and said load side of said circuit interrupting device, and sensing circuitry used to sense the occurrence of said predetermined condition.

15

Claim 35. (original) The modular electrical component according to claim 25, wherein said connecting means comprises a plurality of terminal connections, each terminal connection having:

a first terminal member connectable to one of said plurality of contacts extending from said rear of said removable electrical device; and

a second terminal member connectable to at least one conductor in the electrical wiring system.

Claim 36. (currently amended) A modular electrical component, comprising:  
a base unit having:

25

a receiving channel for a device;

a plurality of first terminal members; and

a plurality of second terminal members connectable to conductors in an electrical wiring system;

a mounting strap having a ground terminal connection for receiving a ground wire and secured to the external surface of a rear cover of said base unit and capable of connecting said base to a junction box in the electrical wiring system;

5 a removable electrical device adapted to nestle within the receiving channel of the base unit and having a plurality of power contacts extending from a rear cover and capable of releasably connecting to said plurality of first terminal members, such that one of the said plurality of contacts releasably connects to one of said plurality of said first terminal members; and

10 a circuit interrupting portion located within the removable electrical device for breaking a conductive path to at least one of the plurality of power contacts.

Claim 37. (previously added) The modular electrical component according to claim 36, wherein said mounting strap has at least one ground terminal connection that extends into said base unit; and

15 wherein said removable electrical device has at least one ground contact extending from said rear cover of the removable electrical device, said at least one ground contact being capable of being releasably connected to said at least one ground terminal connection of the mounting strap.

20 Claim 38. (previously added) The modular electrical component according to claim 36, wherein said removable electrical device comprises a receptacle.

Claim 39. (previously added) The modular electrical component according to claim 36, wherein said removable electrical device comprises a switch.

25 Claim 40. (previously added) The modular electrical component according to claim 36, wherein said removable electrical device comprises a circuit interrupting device.



Claim 41. (previously added) The modular electrical component according to claim 36, wherein said base unit is configured to fit within a single gang junction box in the electrical wiring system.

5        Claim 42. (previously added) The modular electrical component according to claim 36, wherein said base unit is configured to fit within a multiple gang junction box in the electrical wiring system.

10        Claim 43. (currently amended) A modular electrical component, comprising:  
C        a removable electrical device adapted to nestle within a receiving channel of a base unit and having a plurality of power contacts extending from a rear cover of said removable electrical device;

15        a base unit configured to fit within a junction box of an electrical wiring system, said base unit having a receiving channel for receiving the removable electrical device and a plurality of terminal connections, wherein each terminal connection is connectable to at least one conductor in the electrical wiring system and to at least one of said power contacts;

20        a mounting strap having a ground terminal connection secured to the external surface of a rear cover of said base unit and capable of connecting said base unit to the junction box in the electrical wiring system; and

      a circuit interrupting portion located within the removable electrical device for breaking a conductive path to at least one of the plurality of power contacts.

25        Claim 44. (previously added) The modular electrical component according to claim 43, wherein said mounting strap has at least one ground terminal connection that extends into said base unit; and

      wherein said removable electrical device has at least one ground contact  
30        extending from said rear cover of the removable electrical device, said at least one ground contact being capable of being releasably connected to said at least one ground terminal connection of the mounting strap.

Claim 45. (previously added) The modular electrical component according to claim 43, wherein said removable electrical device comprises a receptacle.

5 Claim 46. (previously added) The modular electrical component according to claim 43, wherein said removable electrical device comprises a switch.

10 Claim 47. (previously added) The modular electrical component according to claim 43, wherein said removable electrical device comprises a circuit interrupting device.

c) Claim 48. (previously added) The modular electrical component according to claim 43, wherein each of said terminal connections comprises:  
a first terminal member connectable to one of said plurality of contacts extending from said rear of said removable electrical device; and  
15 a second terminal member connectable to at least one conductor in the electrical wiring system.

Claim 49. (currently amended) A modular electrical component, comprising a removable electrical device adapted to nestle within a receiving channel of a  
20 connecting means and having a plurality of power contacts extending from a rear cover of said removable electrical device;

connecting means configured to fit within a junction box of an electrical wiring system for connecting said plurality of power contacts to at least one conductor in the electrical wiring system and having a receiving channel for receiving the removable  
25 electrical device;

mounting means having a ground terminal connection secured to a rear cover of said connecting means for mounting said connecting means to the junction box in the  
electrical wiring system; and

a circuit interrupting portion for breaking a conductive path to a first power  
30 contact of the plurality of power contacts.

Claim 50. (previously added) The modular electrical component according to claim 49, wherein said removable electrical device has at least one ground contact extending from said rear cover; and

5 wherein said mounting means includes means for connecting said at least one ground contact to a ground of said electrical wiring system.

Claim 51. (previously added) The modular electrical component according to claim 49, wherein said removable electrical device comprises a receptacle.

10 Claim 52. (previously added) The modular electrical component according to claim 49, wherein said removable electrical device comprises a switch.

c  
15 Claim 53. (previously added) The modular electrical component according to claim 49, wherein said removable electrical device comprises a circuit interrupting device.

Claim 54. (previously added) The modular electrical component according to claim 53, wherein said circuit interrupting device comprises:

20 a housing;  
means associated with said plurality of power contacts for conducting electricity between a line side and a load side of said circuit interrupting device;  
circuit interrupting means for breaking continuity between said line side and said load side of said circuit interrupting device upon the occurrence of a predetermined condition; and  
25 reset means for reestablishing electrical continuity between said line side and said load side of said circuit interrupting device.

---

~~Claim 55. (previously added) The modular electrical component according to~~  
claim 49, wherein said connecting means comprises:  
30 a plurality of terminal connections, each terminal connection having:

Serial No. 10/045,541

0267-001-1436CON

a first terminal member connectable to one of said plurality of contacts  
extending from said rear of said removable electrical device; and

a second terminal member connectable to at least one conductor in the  
electrical wiring system.

5